COMBINATION

4040s OD Carbon - 4060s OD Carbon 4060s OD Macrolite - 4060f OD Macrolite/Carbon

Kinetico's combination system combines two, dual function systems, essentially making it four systems in one. Kinetico filters are fitted with a non-electric control valve to provide a continuous flow of filtered water.

It provides a continuous availability of soft and filtered water. This eliminates the need for separate systems, saving money and space. It also simplifies maintenance. Since the media is contained in separate tanks, it can be replaced easily without disturbing or dismantling other parts of the system.

- Dual function system particle filtration and water softening
- Easy installation and maintenance
- · Continuous availability











Over 40 Years Experience



Non-Electric



Twin Tank Design



Metered Regeneration



Soft Water Rinse



Countercurrent Regeneration



Low Salt Consumption





COMBINATION SERIES

4040s OD Carbon - 4060s OD Carbon 4060s OD Macrolite - 4060f OD Macrolite/Carbon

	MACH 4040s OD Carbon	MACH 4060s OD Carbon	MACH 4060s OD Macrolite	MACH 4060f OD Macrolite/Carbon
	1067	1219	1219	1219
	432 203 Measurements in mm	432 203 Measurements in mm	432 203 Measurements in mm	Measurements in mm
Min. Flow	2	2	2	2
Max. Flow@1 bar, I/m	42	44	44	42
Function:	Overdrive	Overdrive	Overdrive	Overdrive
Meter Type	Half / Louver	Half / Louver	Half / Louver	Half / Louver
Disc Selection:	°dH L	°dH L	°dH L	L
1	7 2487	4 8207	3 4743	8207
2	14 1244	8 4103	8 2373	4103
3	20 829	12 2736	13 1582	2736
4	26 622	15 2052	19 1185	2052
5	30 497	18 1641	24 950	1641
6	34 415	21 1368	29 790	1368
7	38 355	24 1172	35 678	1172
8	42 311	26 1026	40 594	1026
Specification:				
Upper media vessel size (litre)	11 L fine mesh cation resin	7 L acid washed carbon	6 L Macrolite	6 L Macrolite
Lower media vessel size (litre)	11 L acid washed carbon	20 L fine mesh cation resin	20 L fine mesh cation resin	11 L acid washed carbon
Inlet/outlet connections	1" to 1,25"	1" to 1,25"	1" to 1,25"	1" to 1,25"
Brine tank size (mm)	Ø457 x 889	Ø457 x 889	Ø457 x 889	
Salt capacity	114 kg	114 kg	114 kg	
Max. Temp.:	49°C	49°C	49°C	49°C
Min./Max. inlet pressure	2,5/8,5 bar	2,5/8,5 bar	2,5/8,5 bar	2,5/8,5 bar
Min. outlet pressure	1,5 bar	1,5 bar	1,5 bar	1,5 bar